

# GN Netcom



For truly innovative features in a traditional call center headset, choose the GN Netcom Contour LX-G. With its variable capsule adjustment, Contour LX-G offers call center professionals the utmost in fit, comfort and stability, with a patented hinge that brings the capsule to a gentle but snug rest behind the earlobe. The Contour LX-G also features a noise-canceling microphone for crystal-clear communication, a non-kink flexible microphone boom for long-term reliability and a choice of comfortable eartips for all-day wearability.

- **Noise-canceling microphone**
- **Over-the-ear comfort**
- **Fully adjustable capsule**
- **Flexible microphone boom**
- **Foam EarTiplets™ and Latex eartips**
- **Two-year "No Fine Print" warranty**



## CONTOUR LX-G

OPTIMUM CALL CENTER COMFORT AND CLARITY.

**GN** Netcom, Inc.

The Contour LX-G headset features a noise-canceling microphone for call clarity, our patented Adjustable Lobe Hinge for custom comfort and stability, and a choice of foam or latex eartip styles.



**Contour LX-G**

There's a GN Netcom amplifier for every need and every application. Like our headsets, all GN Netcom amplifiers feature a two-year warranty.



**The MPA-II Multi-Purpose Amplifier** works on most phone systems with a modular handset connector. The easiest amplifier to set up and use, it features a sliding volume control, headset/handset switch, mute switch and a built-in headset stand. An optional on-line indicator signals when the headset is in use.



**Our 0686 In-line Amplifiers** provide a cost-effective option for standard carbon applications. Incredibly compact, they feature a rotary wheel for a broad range of volume adjustments. Also available with a mute button, **0686M**.



**The 0452 Two-Prong Amplifier** is designed for telephones equipped with a two-prong headset port. Its 3-position volume control locks your volume preference in place.

Also available: The 0911 Two-Prong 6-Wire Amplifier, for push-to-talk dispatch/911 environments; and the HT One Headset Telephone (HT-1), the first professional-quality telephone with an integrated headset—ideal for PBX and CTI applications.

Standard Features	LX-G
Universal Telephone Interface	Δ
Noise-Canceling Microphone	Δ
Flexible Microphone Boom	Δ
Over-The-Ear Comfort	Δ
Adjustable Lobe Hinge™	Δ
Foam & Latex Ear Tiplets	Δ
GN Netcom-compatible Quick Disconnect	Δ
Two-Year "No Fine Print" Warranty	Δ
Great Sound, Comfort, Durability	Δ

Transmit Specifications	
Microphone:	Noise-canceling electret
Frequency Response:	300-3000 Hz
Distortion:	Less than 5%
Current Consumption:	250 μa @ 3 V (DC)
Operating Voltage:	1.5-10 V (DC)

Receive Specifications	
Speaker:	Magnetic
Input Impedance:	300 ohms (typical)
Frequency Response:	300-3,300 Hz
Automatic Gain Control (AGC) Threshold Level with amplifier:	-41 dBV with an input at 1 kHz
Volume Control Range:	18 dB (typical)
Maximum Output:	114 dB spl peak unit

General Specifications	
Operating Temperature:	0°–50° C
Polarity:	Non-polar in amplified applications
Dielectric Withstand Voltage:	5,000 V AC or 7,000 V DC
Safety:	Registered to UL 1459 FCC Parts 68 Registered OSHA Part 1910 subpart S CSA C22.2 No. 225-M90

**GN Netcom, Inc.**

For more information: